

Quality Door and Window Fittings

Residential Door Bolts

856 TYPE 3

D11 0208 Product by FUHR

856 TYPE 3 – Lever Operated – Hook Bolts

One piece 16mm wide steel flat faceplate silver bichromate finish 2170mm overall, enclosed zinc plated lockcase to suit lever and profile cylinder, with latch, deadbolt, 2 roller cams and 2 hook bolts. Also available with 4 hook bolts and no roller cams. Follower 8mm. Centres 92mm. Handle height 1020mm.

- Reversible latch
- Latch sealing pressure adjustable via profile related plates
- Adjustable brass roller cams +/- 1mm provide consistently smooth and reliable engagement into plates
- Roller cam travel 19mm
- Steel Hook Bolt throw 20mm with lockout for strength and security
- Hook bolt sealing pressure adjustable via profile related plates
- Deadbolt throw – 14mm (Backset 30mm)
20mm (Backset 35mm, 40mm, 45mm, 55mm)
- Multipoint function provides enhanced noise reduction and heat insulation
- Profile related plates

Operation

Locking inside/outside	Lift lever engages roller cams and hook bolts into plates, single turn of key throws deadbolt and locks the mechanism, lever returns to horizontal position.
Unlocking inside/outside	Single turn of key retracts deadbolt, depress lever disengages roller cams, hook bolts and retracts latch, lever returns to horizontal position.

A.B.I. Approved




POLICE PREFERRED SPECIFICATION

Part No.	Description	Box Qty.
M6252D60S0	856 Doorbolt 2 Hook Backset 25mm	5
M6302D60S0	856 Doorbolt 2 Hook Backset 30mm	5
M6352D64S0	856 Doorbolt 2 Hook Backset 35mm	5
M6302DF0S0	856 Doorbolt 4 Hook Backset 30mm	5
M6352DF4S0	856 Doorbolt 4 Hook Backset 35mm	5

Options

20mm flat faceplate, 24mm x 6mm U-rail faceplate
 40mm, 45mm and 55mm backset
 25mm deadbolt throw - 35mm and 45mm backset only
 Doorbolt with 2 hooks without roller cams





Quality Door and Window Fittings

Residential Door Bolts

856 TYPE 3

D11 0208 Product by FUHR

- 856 TYPE 3**
- Lever Operated**
- Hook Bolts**

