



Quality Door and Window Fittings

Residential Door Bolts

856 TYPE 6

D12 0907 Product by FUHR

856 TYPE 6 - Lever Operated - Hook With Shoot Bolts

Two piece 16mm wide steel flat faceplate silver bichromate finish 2195mm overall, enclosed zinc plated lockcase to suit lever and profile cylinder, with latch, deadbolt, 2 roller cams, 2 hook bolts, top and bottom shoot bolts.

Follower 8mm. Centres 92mm. Handle height 1020mm.

- Reversible latch
- Latch sealing pressure adjustable via profile related plates
- Adjustable brass roller cams +/- 1mm provide consistently smooth and reliable engagement into plates
- Roller cam travel 19mm
- Steel Hook Bolt throw 20mm with lockout for strength and security
- Hook bolt sealing pressure adjustable via profile related plates
- Top and bottom shoot bolt throw 19mm
- Top and bottom shoot bolt sealing pressure adjustable via profile related plates
- Deadbolt throw - 14mm (Backset 30mm)
20mm (Backset 35mm)
- Multipoint function provides enhanced noise reduction and heat insulation
- Profile related plates

Operation

Locking inside/outside Lift lever engages roller cams, hook bolts and shoot bolts into plates, single turn of key throws deadbolt and locks the mechanism, lever returns to horizontal position.

Unlocking inside/outside Single turn of key retracts deadbolt, depress lever disengages roller cams, hook bolts, shoot bolts and retracts latch, lever returns to horizontal position.

To suit door rebate height 1895mm-2195mm

A.B.I. Approved



Part No.	Description	Box Qty.
M6B6506S	856 Doorbolt Type 6 Backset 30mm	5
M6B6507S	856 Doorbolt Type 6 Backset 35mm	5

Options

DXVL200 200mm Extension





Quality Door and Window Fittings

Residential Door Bolts

856 TYPE 6

D12 0907 Product by FUHR

856 TYPE 6

- Lever Operated
- Hook with Shoot Bolts

