



Quality Door and Window Fittings

# Stable Door

## STABLE DOOR OPTION 2

D24 0907 Product by FUHR

### STABLE DOOR OPTION 2

For some time we have offered an Option 1 Stable Door kit which was based on using an assortment of standard stock parts. Option 2 is a purpose made product consisting of four components which will be sold as a set under one part number.

Profile related strikers are required to complete the package.

2 No. Combined latch/deadbolt plates (handed)

2 No. Roller plates

2 No. Hook plates

Part No.	Description	Box Qty.
M6B6512S	Backset 35mm Stable Door Kit 1500mm overall	5

Multipoint lock designed specifically for Stable Doors. Incorporates all the main Multisafe features. Top door lock is 859 (lever operated/key locking split follower) based with latch, deadbolt, one roller, one hook. Bottom door lock is 855 (key wind) based with deadbolt, one roller, one hook and a top shootbolt. Shootbolt engagement to lock the doors together when fully open.

### Operation

#### To open the complete door from inside/outside.

Unlock both cylinders and depress the lever to release the latch. The two halves of the door will be held together by the shootbolt on the bottom lock.

#### To open the top door from inside/outside.

Unlock cylinder in top door, depress the lever to release the latch, roller and hook.

#### To close and lock the top door from inside/outside

Close top door. Lift lever to engage roller and hook. Key lock top door.

#### To close complete door from inside/outside

Lift lever and key lock top section. Turn key on lower door to engage deadbolt, roller and hook.





Quality Door and Window Fittings

# Stable Door

## STABLE DOOR OPTION 2

D24 0907 Product by FUHR

### STABLE DOOR OPTION 2

